

4/34/1

007514048

WPI Acc No: 1988-147981/198822

Lacquering of wood contg. hardening inhibitors - using
polyurea polyformaldehyde resin to block inhibitor migration and
polyurethane lacquer insulating layer and radical-curing lacquer top coat

Patent Assignee: VEB WISS TECH HOLZV (WISS-N)
Inventor: FINGER K; GOLLE N; HORNING S; MEYER G
Number of Countries: 001 Number of Patents: 001
Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
DD 252983	A	19880106	DD 294793	A	19860930	198822 B

Priority Applications (No Type Date): DD 294793 A 19860930

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
DD 252983	A		2		

Abstract (Basic): DD 252983 A

A process is claimed for lacquering wood which has a hardening inhibiting effect (I), with a hardenable radical-forming protective lacquer (II) using a polyurethane-based insulating lacquer (III); the surface is first treated with an aq. soln. of a radical-crosslinking, film-forming urea-formaldehyde (UF) resin which penetrates the pores; this is dried in, and the surface is then coated with (III) and (II). (I) is esp. rosewood; (II) is an unsatd. polyester lacquer, esp. peroxide-cured; (III) is applied in one or more layers; UF resin is dried to the Resite stage, and the insulating layers are sprayed on.

USE/ADVANTAGE - The process is useful esp. for lacquering tropical woods, contg. quinones and phenols partic. for prodn. of musical instruments, furniture, toys and sports equipment. It prevents such impurities diffusing into (II) during drying or hardening.

0/0

Derwent Class: A82; G02; P42

International Patent Class (Additional): B05D-007/08

Derwent WPI (Dialog® File 351): (c) 2001 Derwent Info Ltd. All rights reserved.

© 2001 The Dialog Corporation plc